
## S**E**LSTICE CAM



## **Camera Specifications**

Video Streaming	Unlimited multiple individual configurable streams
Live resolution	1080p / 720p
Video Compression	H.264
Field of View	110° horizontal, 61° vertical
Onboard Storage	32GB, 128GB or 256GB
Battery	Battery LiFePO4 chemistry, 20Ah Up to 5 days without sun
Power	Camera power: 12.8 VDC, typical 2.65 watts, max 4.39 watts *Indoor Power Supply Charging Specifications: 24V, 1A, 24 watts *Outdoor Power Supply Charging Specifications: 20V, 2A, 40 watts
Enclosure and Options	Polycarbonate IP66-rated enclosure with rugged handle (Steel Gray, Work Zone Orange or Stealth Black) Optically clear glass to maintain visual clarity for optimal imaging
Diagnostic System	LED indicator to monitor power and charging status
Total Weight	11.4 lbs
WiFi Networking Specifications	
Wireless Interface	Internal antenna IEEE 802.11a/b/g/n @ 2.4 GHz, @ 5.2 GHz (channels 36, 40, 44, 48)
Approved Modems	Synology RT2600ac - up to 600 ft. Ubiquity AC Pro - up to 300 ft. Netgear NightHawk AC1900 - up to 275 ft.
Security	Password protection, IP address filtering, HTTPS encryption, IEEE 802.1X (EAP-TLS), network access control, WPA2 Enterprise
Solar Module Specifications	
Power	Max Power: 45 Watts Voltage at Max Power (Vmp): 18 Volts Current at Max Power (Imp): 2.5 Amps
Dimensions	21.1"(W) x 26.2"(H) x 1.38"(D)
Weight	11.01 lbs*

\*Weight doesn't include mount